

The cornucopia of meaningful leads: Applying deep adversarial autoencoders for new molecule development in oncology

Kadurin A., Aliper A., Kazennov A., Mamoshina P., Vanhaelen Q., Khrabrov K., Zhavoronkov A.
Kazan Federal University, 420008, Kremlevskaya 18, Kazan, Russia

Abstract

Recent advances in deep learning and specifically in generative adversarial networks have demonstrated surprising results in generating new images and videos upon request even using natural language as input. In this paper we present the first application of generative adversarial autoencoders (AAE) for generating novel molecular fingerprints with a defined set of parameters. We developed a 7-layer AAE architecture with the latent middle layer serving as a discriminator. As an input and output the AAE uses a vector of binary fingerprints and concentration of the molecule. In the latent layer we also introduced a neuron responsible for growth inhibition percentage, which when negative indicates the reduction in the number of tumor cells after the treatment. To train the AAE we used the NCI-60 cell line assay data for 6252 compounds profiled on MCF-7 cell line. The output of the AAE was used to screen 72 million compounds in PubChem and select candidate molecules with potential anticancer properties. This approach is a proof of concept of an artificially-intelligent drug discovery engine, where AAEs are used to generate new molecular fingerprints with the desired molecular properties.

<http://dx.doi.org/10.18632/oncotarget.14073>

Keywords

Adversarial autoencoder, Artificial intelligence, Deep learning, Drug discovery, Generative adversarial networks

References

- [1] Munos BH, Chin WW. How to revive breakthrough innovation in the pharmaceutical industry. *Sci Transl Med*. 2011; 3:89cm16.
- [2] Mignani S, Huber S, Tomás H, Rodrigues J, Majoral J-P. Why and how have drug discovery strategies in pharma changed? What are the new mindsets? *Drug Discov Today*. 2016; 21:239-49.
- [3] Kola I, Ismail K, John L. Opinion: Can the pharmaceutical industry reduce attrition rates? *Nat Rev Drug Discov*. 2004; 3:711-6.
- [4] Thomas DW, Burns J, Audette J, Carrol A, Dow-Hygelund C, Hay M. Clinical development success rates 2006-2015. San Diego: Biomedtracker/Washington, DC: BIO/Bend: Amplion; 2016.
- [5] Yu MJ. Druggable chemical space and enumerative combinatorics. *J Cheminform*. Springer; 2013; 5:19.

- [6] Vanhaelen Q, Mamoshina P, Aliper AM, Artemov A, Lezhnina K, Ozerov I, Labat I, Zhavoronkov A. Design of efficient computational workflows for in silico drug repurposing. *Drug Discov Today*. 2016;. doi: 10.1016/j.drudis.2016.09.019.
- [7] Oquab M, Bottou L, Laptev I, Sivic J. Learning and Transferring Mid-level Image Representations Using Convolutional Neural Networks. 2014 IEEE Conference on Computer Vision and Pattern Recognition. IEEE; p. 1717-24.
- [8] Putin E, Mamoshina P, Aliper A, Korzinkin M, Moskalev A, Kolosov A, Ostrovskiy A, Cantor C, Vijg J, Zhavoronkov A. Deep biomarkers of human aging: Application of deep neural networks to biomarker development. *Aging (Albany, NY)*. 2016; 8 :1021-33. doi: 10.18632/aging.100968.
- [9] Aliper A, Plis S, Artemov A, Ulloa A, Mamoshina P, Zhavoronkov A. Deep Learning Applications for Predicting Pharmacological Properties of Drugs and Drug Repurposing Using Transcriptomic Data. *Mol Pharm*. 2016; 13:2524-30.
- [10] Mamoshina P, Polina M, Armando V, Evgeny P, Alex Z. Applications of Deep Learning in Biomedicine. *Mol Pharm*. 2016; 13:1445-54.
- [11] Krizhevsky, A, Sutskever, I, Hinton, G. ImageNet classification with deep convolutional neural networks. NIPS'2012.
- [12] Hinton G, Deng L, Yu D, Dahl G, Mohamed A-R, Jaitly N, Senior A, Vanhoucke V, Nguyen P, Sainath T, Kingsbury B. Deep Neural Networks for Acoustic Modeling in Speech Recognition: The Shared Views of Four Research Groups. *IEEE Signal Process Mag*. 29:82-97.
- [13] Huanhuan M, Yue Z. Classification of Electrocardiogram Signals with Deep Belief Networks. 2014 IEEE 17th International Conference on Computational Science and Engineering. IEEE; p. 7-12.
- [14] Jarrett K, Kavukcuoglu K, Ranzato MA, LeCun Y. What is the best multi-stage architecture for object recognition? 2009 IEEE 12th International Conference on Computer Vision. IEEE; p. 2146-53.
- [15] Goodfellow IJ, Warde-Farley D, Mirza M, Courville A, Bengio Y. Maxout Networks. arXiv:1302.4389v4 [stat. ML]. 2013.
- [16] Denton, Emily L., Soumith Chintala, Rob Fergus. Deep Generative Image Models using a? Laplacian Pyramid of Adversarial Networks. *Adv Neural Inf Process Syst*. 2015;: 1486-94.
- [17] van den Oord Matthias Bethge LTA. A note on the evaluation of the generative models. arXiv:1511.01844v3 [stat.ML]. 2016.
- [18] Goodfellow, Ian, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, Yoshua Bengio. Generative adversarial nets. *Adv Neural Inf Process Syst*. 2014;: 2672-80.
- [19] Daniel Jiwoong Im, Chris Dongjoo Kim, Hui Jiang, Roland Memisevic. Generating images with recurrent adversarial Networks. arXiv:1602.05110v4 [cs.LG]. 2016.
- [20] Costello JC, Heiser LM, Georgii E, Gönen M, Menden MP, Wang NJ, Bansal M, Ammad-ud-din M, Hintsanen P, Khan SA, Mpindi J-P, Kallioniemi O, Honkela A, et al. A community effort to assess and improve drug sensitivity prediction algorithms. *Nat Biotechnol*. 2014; 32: 1202-12.
- [21] Azuaje F. Computational models for predicting drug responses in cancer research. *Brief Bioinform*. 2016; doi: 10.1093/bib/bbw065.
- [22] Barretina J, Caponigro G, Stransky N, Venkatesan K, Margolin AA, Kim S, Wilson CJ, Lehár J, Kryukov GV, Sonkin D, Reddy A, Liu M, Murray L, et al. The Cancer Cell Line Encyclopedia enables predictive modelling of anticancer drug sensitivity. *Nature*. 2012; 483:603-7.
- [23] Garnett MJ, Edelman EJ, Heidorn SJ, Greenman CD, Dastur A, Lau KW, Greninger P, Thompson IR, Luo X, Soares J, Liu Q, Iorio F, Surdez D, et al. Systematic identification of genomic markers of drug sensitivity in cancer cells. *Nature*. 2012; 483:570-5.
- [24] Shoemaker RH. The NCI60 human tumour cell line anticancer drug screen. *Nat Rev Cancer*. 2006; 6:813-23.
- [25] Kim S, Thiessen PA, Bolton EE, Chen J, Fu G, Gindulyte A, Han L, He J, He S, Shoemaker BA, Wang J, Yu B, Zhang J, et al. PubChem Substance and Compound databases. *Nucleic Acids Res*. 2016; 44:D1202-13.
- [26] Wang Y, Suzek T, Zhang J, Wang J, He S, Cheng T, Shoemaker BA, Gindulyte A, Bryant SH. PubChem BioAssay: 2014 update. *Nucleic Acids Res*. 2013; 42:D1075-82.
- [27] Lezhnina K, Kovalchuk O, Zhavoronkov AA, Korzinkin MB, Zabolotneva AA, Shegay PV, Sokov DG, Gaifullin NM, Rusakov IG, Aliper AM, Roumiantsev SA, Alekseev BY, Borisov NM, et al. Novel robust biomarkers for human bladder cancer based on activation of intracellular signaling pathways. *Oncotarget*. 2014; 5:9022-32. doi: 10.18632/oncotarget.2493.
- [28] Ozerov IV, Lezhnina KV, Izumchenko E, Artemov AV, Medintsev S, Vanhaelen Q, Aliper A, Vijg J, Osipov AN, Labat I, West MD, Buzdin A, Cantor CR, et al. In silico Pathway Activation Network Decomposition Analysis (iPANDA) as a method for biomarker development. *Nat Commun*. 2016; 7:13427.
- [29] Zhu Q, Izumchenko E, Aliper AM, Makarev E, Paz K, Buzdin AA, Zhavoronkov AA, Sidransky D. Pathway activation strength is a novel independent prognostic biomarker for cetuximab sensitivity in colorectal cancer patients. *Hum Genome Var*. 2015; 2:15009.

- [30] Mitchell JBO. Machine learning methods in chemoinformatics. Wiley Interdiscip Rev Comput Mol Sci. 2014; 4:468-81.
- [31] Lusci A, Pollastri G, Baldi P. Deep architectures and deep learning in chemoinformatics: the prediction of aqueous solubility for drug-like molecules. J Chem Inf Model. 2013; 53:1563-75.
- [32] David Duvenaud, Dougal Maclaurin, Jorge Aguilera-Iparraguirre Rafael Gomez-Bombarelli, Timothy Hirzel, Alan Aspuru-Guzik, Ryan P. Adams. Convolutional Networks on Graphs for Learning Molecular Fingerprints. arXiv:1509.09292v2 [cs.LG]. 2015.
- [33] Steven Kearnes, Kevin McCloskey, Marc Berndl, Vijay Pande, Patrick Riley. Molecular Graph Convolutions: Moving Beyond Fingerprints. arXiv:1603.00856v3 [stat. ML]. 2016.
- [34] Gfeller D, Grosdidier A, Wirth M, Daina A, Michielin O, Zoete V. SwissTargetPrediction: a web server for target prediction of bioactive small molecules. Nucleic Acids Res. 2014; 42:W32-8.
- [35] Mervin LH, Afzal AM, Drakakis G, Lewis R, Engkvist O, Bender A. Target prediction utilising negative bioactivity data covering large chemical space. J Cheminform. 2015; 7:51.
- [36] Izharwallach Michael Dzamba. AtomNet: A Deep Convolutional Neural Network for Bioactivity Prediction in Structure-based Drug Discovery. arXiv:1510.02855v1 [cs.LG]. 2015.
- [37] George E. Dahl, Navdeep Jaitly, Ruslan Salakhutdinov. Multi-task Neural Networks for QSAR Predictions. arXiv:1406.1231v1 [stat.ML]. 2014.
- [38] Thomas Unterthiner, Andreas Mayr, Günter Klambauer, Sepp Hochreiter. Toxicity Prediction using Deep Learning. arXiv:1503.01445v1 [stat.ML]. 2015.
- [39] Ma J, Sheridan RP, Liaw A, Dahl GE, Svetnik V. Deep neural nets as a method for quantitative structure-activity relationships. J Chem Inf Model. 2015; 55:263-74.
- [40] O'Boyle NM, Banck M, James CA, Morley C, Vandermeersch T, Hutchison GR. Open Babel: An open chemical toolbox. J Cheminform. 2011; 3:33.
- [41] Alireza Makhzani, Jonathon Shlens, Navdeep Jaitly, Ian Goodfellow, Brendan Frey. Adversarial Autoencoders. arXiv:1511.05644v2 [cs.LG]. 2016.
- [42] Bishop C. Pattern Recognition and Machine Learning. Springer-Verlag New York; 2006.